

Z MASTER COMMERCIAL 3000 SERIES

| | 74952 | 74953 | 74957 | 74958 | 74959 |
|------------------------------------|--|-------------------------------|---|---|---------------------------------------|
| Engine* at 3600 RPM | 20.5 hp Kawasaki® FX 726cc | 22 hp Kawasaki FX 726cc | 23.5 hp Kawasaki FX 726cc | 25 hp Kohler® Command Pro EFI 747cc | 25 hp Kohler® Command Pro 747cc |
| Electric Start | Standard | | | | |
| Heavy Duty Canister Air Cleaner | Standard | | | | |
| Drive Tires | 23" x 9.5" - 12" | | 24" x 12" - 12" | | |
| Caster Tires | 13" x 5" - 6" pneumatic | 13" x 6.5" - 6" pneumatic | | | |
| Fuel Capacity | 8 gallons | | | | |
| Digital Fuel Gauge | Standard | | | | |
| Digital Hour Meter | Standard | | | | |
| Hydraulic Drive System | Unitized 12 cc pumps & 14.6 cubic inch motors | | Unitized 12 cc pumps w/cooling fans & 14.6 cubic inch motors | | |
| Max Ground Speed (Fwd) | 8.5 mph | | 10 mph | | |
| Seat | Premium Bolstered | | | | |
| Deck Widths | 48" | 52" | 60" | 60" | 72" |
| Cutting Deck | TURBO FORCE® | | | | |
| Deck Depth | 5.5" | | | | |
| Deck Construction | 7-gauge high-strength steel | | | | |
| Bull-nose Bumper | Standard | | | | |
| Adjustable Discharge Baffle | Standard | | | | |
| Rubber Discharge Chute | Standard | | | | |
| 1" Heavy-Duty Spindle Shaft | Standard | | | | |
| Spindle Bearings | Greaseable Ball Bearings | | | | |
| Deck Lift Assist Pedal | Standard | | | | |
| Cutting Height | 1.0" - 5.5" in .25" increments | | | | |
| Anti-Scalp Rollers | 3 standard, 1 optional | | 4 standard, 1 optional | | |

Z MASTER® COMMERCIAL 3000 SERIES



COMMERCIAL ENGINES

Powerful Kawasaki & Kohler commercial-grade engines provide professional quality performance. Heavy-duty canister air filtration system protects engine from contaminants and prolongs product life.



TOUGH SPINDLE ASSEMBLIES

Toro's rugged spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.



OPERATOR COMFORT

The thick cushions and padded armrests improve operator productivity by reducing fatigue, and the standard lift assist pedal allows for fast and easy deck height adjustments.



Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

490-8744 ©2014 The Toro Company. All rights reserved.

*The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.